

ELECTRIC FAN HEATERS



B 2
B 3



B 2PTC



B 5
B 9
B 15
B 22

- ▼ Automatic reset
- ▼ Built-in room thermostat
- ▼ No oxygen consumption
- ▼ No fumes, no odours, no humidity
- ▼ Summer-Winter switch for ventilation only
- ▼ Low noise
- ▼ Motor with thermal protection
- ▼ Overheat thermostat
- ▼ Adjustable heat



OPTIONAL ACCESSORIES:



Extension cord

B 5, B 9 - 5 m - **4511.031**
 B 5, B 9 - 10 m - **4511.032**
 B 15, B 22 - 5 m - **4511.033**
 B 15, B 22 - 10 m - **4511.034**



SPECIFICATIONS		B 2PTC	B 2	B 3	B 5	B 9	B 15	B 22
Heating power	kW	1/2	1/2	1,65/3,3	2,5/5	4,5/9	7,5/15	11/22
	Btu/h	3.400-6.800	3.400-6.800	5.630-11.260	8.530-17.000	515.350-30.700	25.600-51.200	37.530-75.100
	kcal/h	860-1.720	860-1.720	1.430-2.860	2.150-4.300	3.870-7.740	6.450-12.900	9.460-18.900
Air displacement	m ³ /h	97	184	510	510	800	1.700	2.400
Power supply	V	230	230	230*	3N 400	3N 400	3N 400	3N 400
Frequency	Hz	50	50-60	50-60	50-60	50-60	50-60	50-60
Plug (male) from heater side		16A/3P	16A/3P	16A/3P	16A/5P	16A/5P	32A/5P	32A/5P
Rated current	A	8,7	8,7	14,5	7,2	13	22	32
Switch pos. 1		1 kW	off	off	off	off	off	off
Switch pos. 2		2 kW	fan	fan	fan	fan	fan	fan
Switch pos. 3/4	kW	-	1,0/2,0	1,65/3,3	2,5/5,0	4,5/9,0	7,5/15	11,0/22,0
Thermostat control		included	included	included	included	included	included	included
Temperature range	°C	0-40	5-35	5-35	5-35	5-35	5-35	5-35
Protection		IP21	IP24	IP24	IP24	IP24	IP24	IP24
Packaging dimension (l x w x h)	mm	200 x 200 x 200	240 x 220 x 260	280 x 270 x 440	370 x 310 x 390	420 x 330 x 430	370 x 480 x 530	380 x 550 x 630
Net/gross weight	kg	1,9/2,1	3,7/4,2	5,1/5,7	6,4/6,8	9,3/10,3	15/15,9	20/22,8
Pallet	pcs	160	75	48	40	24	15	12

* 110 V available