

EFI 75XX & UB 20XX



UB 20xx



EFI 75xx



- ATEX explosion-proof ventilator
- For harsh working conditions
- PC/ABS antistatic casing, weatherproof, flame retardant and chemical resistant
- High air flow
- Easy transport with comfortable handle
- Possibility to connect a flex tube
- Effective protection against dust and water
- Safely blow or exhaust hazardous gases with minimal risk of the fan causing a spark
- ATEX certification: II 2 G Ex db eb IIB T6 Gb, II 2 G Ex IIB T6 Gb, Zone 1+2

Optional accessories



Flex tube
antistatic, 7.6m
UB 20xx - Ø230mm -
1250099
EFi 75xx - Ø305mm -
1250066



Power cable adaptor
1.5m
UB 20xx, EFi 75xx -
1450290



Duct canister antistatic incl. duct
7.6m, Ø205mm -
UB 20xx - **1250211**

Specifications	Units	UB 20xx	EFi 75xx
Air flow	m ³ /h	1,392	4,250
Max. air pressure	Pa	195	314
Fan	type	Axial	Axial
Fan speed		1	1
Power consumption	W	250	560
Power supply	V/Hz	230/1ph/50	220-240/1ph/50-60
Sound level	dB(A)	74	89
Flex tube diametre	mm	205	305
Protection		IP55	IP55
Product size (l x w x h)	mm	330 x 305 x 355	406 x 381 x 406
Box size (l x w x h)	mm	450 x 400 x 530	450 x 500 x 520
Net/gross weight	kg	8.2/15	20
Pallet	pcs	8	6