



Single Inlet Centrifugal Fans 1450 RPM

- Low, medium pressure.
- High quality, advanced technology.
- Housing made of **galvanized pressed steel**.
- Impeller with sparse wide scooped blades for easy cleaning and prevention of oily residue buildup.
- Optional fan mounting inside a Fan Section, page 32.
- Electrical wiring diagram see page 25.
- Performance Curves for all fans on pages 20-22.
- Greater horsepower available upon request.

Application : Suitable for industrial applications, commercial kitchens, steak houses etc

Technical Characteristics 1450 RPM

Power		Inlet (mm) Flange Ø	Outlet Flange		Air Flow m³/h	Voltage VOLT	Price
HP	kW		Internal mm	External mm			
0,5	0,37	200	205 x 245	255 x 295	2.500	230/400	⌘
1,0	0,75	250	225 x 345	275 x 395	5.000	230/400	⌘
1,5	1,1	250	255 x 345	305 x 395	6.000	230/400	⌘
2,0	1,5	300	275 x 405	325 x 455	8.000	230	⌘
2,0	1,5	300	275 x 405	325 x 455	8.000	400	⌘
3,0	2,2	300	275 x 405	325 x 455	9.000	400	⌘
3,0	2,2	300	275 x 405	325 x 455	9.000	230	⌘
3,0	2,2	350	325 x 405	375 x 455	10.000	400	⌘
4,0	3,0	350	325 x 455	375 x 505	11.000	400	⌘
5,5	4,0	350	325 x 455	375 x 505	13.000	400	⌘
7,5	5,5	450	570 x 440	630 x 500	16.000	400	⌘



Caution: 400V (three phase) motors should be protected by thermal contacts.

